



## NTN DRIVESHAFT ANDERSON, INC.



7217BG Bearing 2D drawings and 3D CAD models

85,000 mm x 150,000 mm x 28,000 mm NTN  
7217BG angular contact ball bearings

Bearing No. 7217BG

Size	85x150x28 mm
Bore Diameter	85,000 mm
Outer Diameter	150,000 mm
Width	28,000 mm
d	85,000 mm
D	150,000 mm
B	28,000 mm
C	28,000 mm
a	63.5 mm
Contact angle	40 °
rs min	2 mm
r1s min	1 mm
Radial clearance class	CN
Mass	1.82 kg
Dynamic load, C	90 kN
Static load, C0	80.5 kN
Fatigue limit load, Cu	3.4 kN
Nlim (oil)	5,300 rpm
Nlim (grease)	4,000 rpm
Min operating temperature, Tmin	-40 ° C
Max operating temperature, Tmax	120 ° C
da min	95 mm
db min	90.5 mm
Da max	140 mm



## NTN DRIVESHAFT ANDERSON, INC.

Db max	144.5 mm
r1a max	1 mm
ra max	2 mm
Category	Angular Contact Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	1.855
EAN	4547359445572
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Steel
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Mounting Arrangement	Universal
Inch - Metric	Metric
Long Description	85MM Bore; 150MM Outside Diameter; 28MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1   ISO P0; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531



## NTN DRIVESHAFT ANDERSON, INC.

Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	7217BG
Weight / LBS	4.097
Width	1.102 Inch   28 Millimeter
Outside Diameter	5.906 Inch   150 Millimeter
Bore	3.346 Inch   85 Millimeter
bore diameter:	85 mm
radial static load capacity:	80500 N
outside diameter:	150 mm
operating temperature range:	-40 to 120 ° C
overall width:	28 mm
cage material:	Steel
contact angle:	40 °
outer ring width:	28 mm
row type & fill slot:	Single-Row Non-Fill Slot
maximum rpm:	5300 rpm
internal clearance:	C0
finish/coating:	Uncoated
bore type:	Round
precision rating:	ISO Class 0
closure type:	Open
fillet radius:	2 mm
snap ring included:	Without Snap Ring
series:	72B
bearing material:	High Carbon Chrome Steel
weight:	1.854 kg
radial dynamic load capacity:	90000 N



## NTN DRIVESHAFT ANDERSON, INC.

manufacturer product page:

[Click here](#)