



NTN DRIVESHAFT ANDERSON, INC.



39,688 mm x 73,025 mm x 22,098 mm NSK
M201047/M201011 tapered roller bearings

Bearing No. M201047/M201011

M201047/M201011 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|-------------------------|
| Size | 39.688x73.025x25.654 mm |
| Bore Diameter | 39,688 mm |
| Outer Diameter | 73,025 mm |
| Width | 25,654 mm |
| d | 39,688 mm |
| D | 73,025 mm |
| T | 25,654 mm |
| B | 22,098 mm |
| C | 21,336 mm |
| ra1 max. | 2,3 mm |
| a | 19,7 mm |
| r min. | 0,8 mm |
| r1 min. | 2,3 mm |
| Da | 64 mm |
| db | 48 mm |
| ra max. | 0,8 mm |
| da | 45,5 mm |
| Db | 69 mm |
| Weight | 0,435 Kg |
| Basic dynamic load rating (C) | 62,5 kN |
| Basic static load rating (C0) | 80 kN |
| (Grease) Lubrication Speed | 5000 r/min |
| (Oil) Lubrication Speed | 6700 r/min |
| Calculation factor (e) | 0,33 |
| Calculation factor (Y0) | 0,99 |



NTN DRIVESHAFT ANDERSON, INC.

| | |
|------------|-------------------|
| LangID | 1 |
| ALP23 | 0 |
| outer r | 2.3 |
| ALP22 | 0 |
| D_ | 73.025 |
| ALP21 | 25 |
| SHOG_yobi | M201047R/M201011R |
| RAr | 156.626 |
| inner r | 0.8 |
| GRS rpm | 5000 |
| D_b | 69 |
| D_a | 64 |
| DE_ | 63.393 |
| SLR | 16.5 |
| Prod_Type3 | TRBSR_ID_A |
| BETA_ | 1 |
| ALPHA_ | 12.5 |
| SDM_ | 56.623 |
| DA1 | 8.2 |
| DA2 | 7.339 |
| hidYobi | M201047/M201011 |
| Y1 | 1.8 |
| B_ | 22.098 |
| Oil rpm | 6700 |
| hidTable | ecat_NSTPRI |
| Y0 | 0.99 |
| inner ra | 0.8 |
| outer rb | 2.3 |
| C0 | 80 |
| CUP | 0.169 |
| e | 0.33 |
| DA_ | 7.771 |
| | |



NTN DRIVESHAFT ANDERSON, INC.

| | |
|-------|-----------------|
| BET21 | 3 |
| BET22 | 0 |
| BET23 | 0 |
| Z_ | 18 |
| C_ | 21.336 |
| yobi | M201047/M201011 |
| KBRG | 3161 |
| CONE | 0.266 |
| DI_ | 48.929 |