



NTN DRIVESHAFT ANDERSON, INC.



95,25 mm x 190,5 mm x 57,531 mm NSK
864/854 tapered roller bearings

Bearing No. 864/854

864/854 Bearing 2D drawings and 3D CAD models

Size	95.25x190.5x57.15 mm
Bore Diameter	95,25 mm
Outer Diameter	190,5 mm
Width	57,15 mm
d	95,25 mm
D	190,5 mm
T	57,15 mm
B	57,531 mm
C	44,45 mm
ra1 max.	3,3 mm
a	41,8 mm
r min.	8 mm
r1 min.	3,3 mm
Da	170 mm
db	108 mm
ra max.	8 mm
da	123 mm
Db	174 mm
Weight	7,12 Kg
Basic dynamic load rating (C)	355 kN
Basic static load rating (C0)	500 kN
(Grease) Lubrication Speed	1900 r/min
(Oil) Lubrication Speed	2600 r/min
Calculation factor (e)	0,33
Calculation factor (Y0)	0,99



NTN DRIVESHAFT ANDERSON, INC.

LangID	1
ALP23	0
outer r	3.3
ALP22	8
D_	190.5
ALP21	25
SHOG_yobi	864/854
RAr	397.977
inner r	8
GRS rpm	1900
D_b	174
D_a	170
DE_	163.935
SLR	40
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	12.567
SDM_	144.027
DA1	21.992
DA2	19.79
hidYobi	864/854
Y1	1.8
B_	57.531
Oil rpm	2600
hidTable	ecat_NSTPRI
Y0	0.99
inner ra	8
outer rb	3.3
C0	500
CUP	2.55
e	0.33
DA_	20.896



NTN DRIVESHAFT ANDERSON, INC.

BET21	3
BET22	10
BET23	0
Z_	17
C_	44.45
yobi	864/854
KBRG	3161
CONE	4.57
DI_	123.382